MULTI PURPOSE SEAL

Anglo Multi Purpose Seal penetrates deep into dusty porous concrete and hardens to provide a dustproofed surface.

Anglo Multi Purpose Seal is a fine particle, tough acrylic compound that penetrates deep into dusty, porous concrete and hardens to provide a dustproofed surface. Solvent free, virtually odourless and non-flammable, it is easily applied to new or old concrete surfaces using a soft broom.

Ideal for many porous surfaces including:-

- **Concrete**

- **Screeds**

- **Block Paving**

- **Brick, Blockwork and Plaster Walls**

SOLVENT FREE

PROFESSIONAL QUALITY

PRODUCT INFORMATION

APPEARANCE
Anglo Multi Purpose Seal is a fine particle, tough, acrylic compound that may have a slight darkening effect on some substrates.

AVAILABILITY
5 and 25 litre units.

LIMITATIONS
Anglo Multi Purpose Seal is suitable only for bare unsealed porous surfaces. Please contact our Technical Department if you require further information.

SURFACE PREPARATION
The surface to be treated must be dry, free from all loose material, and previous coatings. Oil and grease should be removed with Anglo Multi-Purpose Degreaser or similar emulsifying degreasant and the area hosed off with water and allowed to dry. The surface must be porous to allow the Anglo Multi Purpose Seal to penetrate. If there is doubt that the substrate is absorbent, pour some water onto the surface. If the water is easily absorbed, the surface is suitable for treating with Anglo Multi Purpose Seal.
New concrete should not be treated until the surface is sufficiently dry to absorb the solution (usually at least 7 days in good drying conditions).

APPLICATION
Apply within a range of 10ºC - 30ºC. Do not use at temperatures of less than 10ºC. Pour directly onto the floor from the container. Use a soft broom to distribute the solution, working it well into the surface. Ensure that the surface has absorbed as much solution as it can. Avoid ponding, i.e. do not allow any surplus unabsorbed solution to remain and subsequently dry on the surface. Use the broom to sweep any excess solution onto adjacent areas. One coat is normally sufficient on average quality concrete. A second coat may be required on exceptionally porous substrates. Allow the surface 12 -16 hours to dry before making a second application.

COVERAGE
5 litres of Anglo Multi Purpose Seal will treat approximately 30m· with one application depending upon the porosity of the substrate.

CURING
Anglo Multi Purpose Seal will accept foot and light traffic after 12 hours, and will be fully cured after 24 hours. Do not wash the treated surface for 48 hours. These curing periods assume a temperature of 15ºC - 30ºC and good ventilation.

SAFETY PRECAUTIONS
All product labels provide general safety information. Material Safety Data Sheets are available.

STORAGE
Store at a temperature range of 10ºC - 30ºC. Do not allow the product to freeze.

SHELF LIFE
At least two years in unopened manufacturer's containers.

ANGLO SOLVENT FREE DEGREASER
For preparatory degreasing. A super penetrating degreasant that removes oil and grease from concrete surfaces.
Coverage approximately 2m2 per litre.

ORDERING
Available from stockists throughout the UK. All Anglo products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Anglo products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by the Company.

All information is based on results gained from experience and testing and is believed to be accurate, but it is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control.