



## SAFETY DATA SHEET

### Anglo Asphalt Restorer

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME                      Anglo Asphalt Restorer

SUPPLIER                              Anglo Building Products Ltd  
 RUST-OLEUM UK Ltd  
 Unit 6, Spitfire Close  
 Coventry Business Park  
 Coventry  
 CV5 6UR  
 +44 (0) 2476 717 329  
 +44 (0) 2476 718 930  
 info.uk@ro-m.com

#### 2 HAZARDS IDENTIFICATION

Flammable. Repeated exposure may cause skin dryness or cracking.

CLASSIFICATION                      R10, R66.

#### ENVIRONMENT

The product is not expected to be hazardous to the environment.

#### PHYSICAL AND CHEMICAL HAZARDS

The product is flammable and oxidising, and heating may generate vapours which may form explosive vapour/air mixtures.

#### HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Product has a defatting effect on skin.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BAS 40	265-150-3	64742-48-9	30-60%	Xn;R65. R10,R66.
Distillates (Petroleum) Hydrotreated Light: Kerosine unspecified - benzene free		64742-47-8	10-30%	Xn;R65. R10,R66.

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

The Data Shown is in accordance with the latest EC Directives.

#### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. If respiratory problems, artificial respiration/oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

#### INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Immediately rinse mouth and provide fresh air. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention.

#### SKIN CONTACT

Use appropriate hand lotion to prevent defatting and cracking of skin. Remove affected person from source of contamination. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Get medical attention promptly if symptoms occur after washing.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use: Alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

## Anglo Asphalt Restorer

### SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

### SPECIFIC HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container

### SPILL CLEAN UP METHODS

Keep combustibles away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Wash contaminated area with water. Wash thoroughly after dealing with a spillage.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Do not use contact lenses. Avoid spilling, skin and eye contact. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Store under well-ventilated conditions at a temperature below 25°C.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

### HAND PROTECTION

Protective gloves and goggles must be used if there is a risk of direct contact or splash.

### EYE PROTECTION

Contact lenses should not be worn when working with this chemical! Wear approved safety goggles.

### OTHER PROTECTION

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

### HYGIENE MEASURES

Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Misc. colours
ODOUR	Hydrocarbon
SOLUBILITY	Insoluble in water

**Anglo Asphalt Restorer**

BOILING POINT (°C)	>150C	RELATIVE DENSITY	<1.0
FLASH POINT (°C)	36C	VOLATILE ORGANIC COMPOUND (VOC)	>50%

**10 STABILITY AND REACTIVITY**

## STABILITY

No particular stability concerns.

## CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

## HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**11 TOXICOLOGICAL INFORMATION**

## INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

## INGESTION

Gastrointestinal symptoms, including upset stomach.

## SKIN CONTACT

Repeated exposure may cause skin dryness or cracking.

## EYE CONTACT

Irritating and may cause redness and pain.

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

The product is not expected to be hazardous to the environment.

**13 DISPOSAL CONSIDERATIONS**

## GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

## DISPOSAL METHODS

Absorb in vermiculite or dry sand, dispose in licensed hazardous waste. Make sure containers are empty before discarding (explosion risk).

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	3Y
CEPIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	III	EMS	F-E, S-E
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	III		

## Anglo Asphalt Restorer

---

### 15 REGULATORY INFORMATION

---

RISK PHRASES

R10	Flammable.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

---

### 16 OTHER INFORMATION

---

REVISION DATE                      27/04/2007

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R10	Flammable.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.