



SAFETY DATA SHEET

Anglo Epoxy Bond - resin

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Epoxy Bond - resin

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
C13/15 alkyglycidyl ether		68081-84-5	1-5%	Xi;R36/38. N;R51/53. R43.
DI-ISOBUTYL KETONE	203-620-1	108-83-8	< 1%	R10 Xi;R37
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	30-60%	R43 Xi;R36/38 N;R51/53
Hexanediglycidyl ether	240-260-4	16096-31-4	< 1%	Xi;R36/38. R43,R52/53.
ISO-BUTANOL	201-148-0	78-83-1	< 1%	R10 Xi;R37/38,R41 R67
Solvent naphtha(petroleum), light aromatic,<0.1% benzene	265-199-0	64742-95-6	< 1%	Xn;R65. Xi;R37. N;R51/53. R10.
XYLENE	215-535-7	1330-20-7	< 1%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

Anglo Epoxy Bond - resin

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
DI-ISOBUTYL KETONE	OES	25 ppm	148 mg/m3		
ISO-BUTANOL	OES	50 ppm	154 mg/m3	75 ppm	231 mg/m3
XYLENE	OES	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Brown		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	> 200C	RELATIVE DENSITY	> 1.1
VOLATILE BY VOL. (%)	< 0.1%		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

Anglo Epoxy Bond - resin

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	9		
PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.		
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	9	ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III	HAZARD No. (ADR)	90
ADR LABEL NO.	9	HAZCHEM CODE	3Z
CEFIC TEC(R) NO.	90GM6-III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
EMS	F-A, S-F	MFAG	See Guide
MARINE POLLUTANT		UN NO. AIR	3082



AIR CLASS	9	AIR PACK GR.	III
-----------	---	--------------	-----

15 REGULATORY INFORMATION

LABELLING

Anglo Epoxy Bond - resin



Irritant



Dangerous for the environment

CONTAINS C13/15 alkylglycidyl ether
EPOXY RESIN (Number average MW <= 700)

RISK PHRASES

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S57	Use appropriate containment to avoid environmental contamination.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS
Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE
Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES
Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 06/01/2009

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.



SAFETY DATA SHEET

Anglo Epoxy Bond - curing agent

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Epoxy Bond - curing agent

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Causes burns. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION C;R34. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BENZYL ALCOHOL	202-859-9	100-51-6	5-10%	Xn;R20/22
m-Phenylenebis(methylamine)	216-032-5	1477-55-0	1-5%	Xn;R20/22. C;R35. R43,R52/53.
Polyamide (Unirez)			30-60%	C;R34. N;R51/53. R43.
TETRAETHYLENEMPENTAMINE	203-986-2	112-57-2	1-5%	C;R34 Xn;R21/22 R43 N;R51/53
TRIETHYLENETETRAMINE	203-950-6	112-24-3	1-5%	C;R34 Xn;R21 R43 R52/53

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Remove victim immediately from source of exposure. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention immediately. Continue to rinse.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Fire creates: Toxic gases/vapours/fumes of Carbon monoxide (CO). Carbon dioxide (CO₂).

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

Anglo Epoxy Bond - curing agent

ENVIRONMENTAL PRECAUTIONS

Do not allow ANY environmental contamination.

SPILL CLEAN UP METHODS

DO NOT TOUCH SPILLED MATERIAL! Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Corrosive storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash, quick drench.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Amber		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	> 100C	RELATIVE DENSITY	> 1.0
VOLATILE BY VOL. (%)	>0.1%	FLASH POINT (°C)	> 100C

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

Anglo Epoxy Bond - curing agent

INHALATION

Harmful by inhalation. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

INGESTION

Harmful if swallowed. May cause burns in mucous membranes, throat, oesophagus and stomach.

SKIN CONTACT

Causes burns. Harmful in contact with skin.

EYE CONTACT

Causes burns.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	8		
PROPER SHIPPING NAME	AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S (Polyamide (Unirez), m-Phenylenebis(methylamine))		
UN NO. ROAD	2735	UK ROAD PACK GR.	III
ADR CLASS NO.	8	ADR CLASS	Class 8: Corrosive substances.
ADR PACK GROUP	III	HAZARD No. (ADR)	80
ADR LABEL NO.	8	HAZCHEM CODE	2X
CEFIC TEC(R) NO.	80GC7-II+III	RID CLASS NO.	8
RID PACK GROUP	III	UN NO. SEA	2735
IMDG CLASS	8	IMDG PAGE NO.	8109-2 (UK)
IMDG PACK GR.	III	EMS	F-A, S-B
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	2735	AIR CLASS	8
AIR PACK GR.	III		

15 REGULATORY INFORMATION

LABELLING



Corrosive



Dangerous for the environment

CONTAINS

m-Phenylenebis(methylamine)
 Polyamide (Unirez)
 TETRAETHYLENEPENTAMINE
 TRIETHYLENETETRAMINE

RISK PHRASES

R34 Causes burns.
 R43 May cause sensitisation by skin contact.

Anglo Epoxy Bond - curing agent

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

- S25 Avoid contact with eyes.
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
- S57 Use appropriate containment to avoid environmental contamination.
- S60 This material and its container must be disposed of as hazardous waste.
- S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 06/01/2009

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

- R20/22 Harmful by inhalation and if swallowed.
- R21 Harmful in contact with skin.
- R21/22 Harmful in contact with skin and if swallowed.
- R34 Causes burns.
- R35 Causes severe burns.
- R43 May cause sensitisation by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.