



SAFETY DATA SHEET

Anglo Epoxy Highbuild - resin

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Epoxy Highbuild - resin

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. R43. N;R51/53.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	< 1%	R10 Xi;R36
BUTYL ACETATE -norm	204-658-1	123-86-4	< 1%	R10 R66 R67
C13/15 alkyglycidyl ether		68081-84-5	5-10%	Xi;R36/38. N;R51/53. R43.
DI-ISOBUTYL KETONE	203-620-1	108-83-8	< 1%	R10 Xi;R37
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	60-100%	R43 Xi;R36/38 N;R51/53
Hexanediglycidyl ether	240-260-4	16096-31-4	1-5%	Xi;R36/38. R43,R52/53.
ISO-BUTANOL	201-148-0	78-83-1	< 1%	R10 Xi;R37/38,R41 R67
Solvent naphtha(petroleum), light aromatic,<0.1% benzene	265-199-0	64742-95-6	1-5%	Xn;R65. Xi;R37. N;R51/53. R10.
XYLENE	215-535-7	1330-20-7	< 1%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

Anglo Epoxy Highbuild - resin

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
2-METHOXY-1-METHYLETHYL ACETATE	OES	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)
BUTYL ACETATE -norm	OES	150 ppm	724 mg/m3	200 ppm	966 mg/m3
DI-ISOBUTYL KETONE	OES	25 ppm	148 mg/m3		
ISO-BUTANOL	OES	50 ppm	154 mg/m3	75 ppm	231 mg/m3
XYLENE	OES	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Thick, cloudy fluid		
COLOUR	Amber		
ODOUR	No characteristic odour.		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	>1.0	VOLATILE ORGANIC COMPOUND (VOC)	nil

10 STABILITY AND REACTIVITY

Anglo Epoxy Highbuild - resin

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	9		
PROPER SHIPPING NAME	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700), C13/15 alkylglycidyl ether)		
UN NO. ROAD	3082	UK ROAD PACK GR.	III
ADR CLASS NO.	9	ADR CLASS	Class 9: Miscellaneous dangerous substances and articles.
ADR PACK GROUP	III	HAZARD No. (ADR)	90
ADR LABEL NO.	9	HAZCHEM CODE	3Z
CEFIC TEC(R) NO.	90GM6-III	RID CLASS NO.	9
RID PACK GROUP	III	UN NO. SEA	3082
IMDG CLASS	9	IMDG PACK GR.	III
EMS	F-A, S-F	MFAG	See Guide
MARINE POLLUTANT		UN NO. AIR	3082



AIR CLASS	9	AIR PACK GR.	III
-----------	---	--------------	-----

15 REGULATORY INFORMATION

Anglo Epoxy Highbuild - resin

LABELLING



Irritant



Dangerous for the environment

CONTAINS

C13/15 alkyglycidyl ether
 EPOXY RESIN (Number average MW <= 700)
 Hexanediglycidyl ether

RISK PHRASES

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S57	Use appropriate containment to avoid environmental contamination.
S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 08/12/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.



SAFETY DATA SHEET

Anglo Epoxy High Build - curing agent

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Epoxy High Build - curing agent

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Harmful if swallowed. Causes burns. May cause sensitisation by skin contact.

CLASSIFICATION Xn;R22. C;R34. R43.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BENZYL ALCOHOL	202-859-9	100-51-6	10-30%	Xn;R20/22
ISOPHORONEDIAMINE	220-666-8	2855-13-2	10-30%	C;R34 Xn;R21/22 R43 R52/53
Salicylic acid		69-72-7	1-5%	Xn;R20/22. Xi;R41.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Rinse the skin immediately with lots of water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

UNUSUAL FIRE & EXPLOSION HAZARDS

No unusual fire or explosion hazards noted.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not let washing down water contaminate ponds or waterways.

7 HANDLING AND STORAGE

Anglo Epoxy High Build - curing agent

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Corrosive storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Polyvinylidene chloride/Polyethylene (PVD/PE).

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

Wear appropriate clothing to prevent skin contamination or freezing. Provide eyewash station.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes wet.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Thick, cloudy fluid		
COLOUR	Misc. colours		
SOLUBILITY	Slightly soluble in water.		
BOILING POINT (°C)	> 200C	RELATIVE DENSITY	>1.0
VAPOUR PRESSURE	>66 Pa @20C	VOLATILE BY VOL. (%)	>5%
FLASH POINT (°C)	>100C		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Reacts violently with strong oxidising substances.

HAZARDOUS POLYMERISATION

Will not polymerise.

HAZARDOUS DECOMPOSITION PRODUCTS

Ammonia or amines.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system. May cause sensitisation by inhalation. May cause respiratory allergy.

INGESTION

Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

SKIN CONTACT

May cause allergic contact eczema. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause sensitisation by skin contact. Causes burns. Harmful in contact with skin.

EYE CONTACT

Extreme irritation of eyes and mucous membranes, including burning and tearing. Causes burns.

Anglo Epoxy High Build - curing agent

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses. Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	Isophorone diamine solution		
UN NO. ROAD	2289	ADR CLASS NO.	8
ADR CLASS	Class 8: Corrosive substances.	ADR PACK GROUP	III
HAZARD No. (ADR)	80	ADR LABEL NO.	8
HAZCHEM CODE	3X	CEFIC TEC(R) NO.	80G15
RID CLASS NO.	8	RID PACK GROUP	III
UN NO. SEA	2289	IMDG CLASS	8
IMDG PAGE NO.	8108-2	IMDG PACK GR.	!!!
EMS	8-05	MFAG	320
MARINE POLLUTANT	No.	UN NO. AIR	2289
AIR CLASS	8	AIR PACK GR.	III

15 REGULATORY INFORMATION

LABELLING



Corrosive



Harmful

CONTAINS

ISOPHORONEDIAMINE

RISK PHRASES

R22	Harmful if swallowed.
R34	Causes burns.
R43	May cause sensitisation by skin contact.

SAFETY PHRASES

S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
S60	This material and its container must be disposed of as hazardous waste.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

Anglo Epoxy High Build - curing agent

16 OTHER INFORMATION

REVISION DATE 08/12/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

R20/22	Harmful by inhalation and if swallowed.
R21/22	Harmful in contact with skin and if swallowed.
R34	Causes burns.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.