



SAFETY DATA SHEET

5220 EPOXY Shield ® Sealer

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- Product name and/or code** : 5220 EPOXY Shield ® Sealer
Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands
NV Martin Mathys, Kolenbergstraat 23, B-3545 Zelem, Belgium
- Emergency phone number** : Rust-Oleum: +31(0)165-593636; Fax +31(0)165-593600
Martin Mathys: +32(0)13-460200; Fax +32(0)13-460201
- e-Mail address of person responsible for this SDS** : rpmeurohas@ro-m.com
- Product use** : Floorcoating. Primer .

2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

- Classification** : Not classified.
- Additional warning phrases** : Safety Data Sheet available for professional user on request.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name	CAS #	%	EU no.	Classification
2-butoxyethanol	111-76-2	5 - 10	203-905-0	Xn; R20/21/22 Xi; R36/38 [1] [2]
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Due to the organic solvents content of the preparation:
Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. HANDLING AND STORAGE

- Handling** : Due to the organic solvents content of the preparation:
- Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from heat and direct sunlight.
- Due to the organic solvents content of the preparation:
Keep away from: oxidizing agents, strong alkalis, strong acids.
No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Do not empty into drains.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Ingredient name

2-butoxyethanol

Occupational exposure limits

EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.
STEL: 50 ppm 15 minute(s).
TWA: 25 ppm 8 hour(s).

Exposure controls/personal protection

- Occupational exposure controls** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapor filter (Type A) (EN 141) .
- Hand protection** : Recommended: Disposable vinyl gloves.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
Recommended: safety glasses with side-shields
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: disposable overall
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : Liquid. [Emulsion.]
- Odor** : Ammoniacal. [Slight]
- Boiling point** : >100°C (>212°F)
- Volatility %** : 70% (v/v), 67.6% (w/w)
- Relative density (kg/L)** : 1

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. TOXICOLOGICAL INFORMATION

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LD50 Intraperitoneal	Rat	220 mg/kg	-
	LDLo Oral	Rat	1500 mg/kg	-
	TDLo Unreported	Rat	250 mg/kg	-
	TDLo Oral	Rat	500 mg/kg	-
	LC50 Inhalation	Rat	2900 mg/m ³	7 hours
	Vapor			
	LC50 Inhalation Gas.	Rat	450 ppm	4 hours

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Aquatic ecotoxicity

Ingredient name	Result	Species	Exposure
2-butoxyethanol	Acute EC50 5000 mg/L	Daphnia - Daphnia magna	24 hours
	Acute LC50 1575 mg/L	Fish - Goldfish - Carassius auratus	48 hours
	Acute LC50 1490 mg/l Fresh water	Fish - Bluegill - Lepomis macrochirus - 33 to 75 mm	96 hours
	Acute LC50 1250 mg/l Marine water	Fish - Inland silverside - Menidia beryllina - 40 to 100 mm	96 hours

Ecological information

Biodegradability

Ingredient name	Test	Result	Dose	Inoculum
2-butoxyethanol	OECD 301E	>70 % - Readily - 28 days	-	-
	-	32.27 % - Inherent - 5 days	-	-

Conclusion/Remark : This product has not been tested for biodegradation.

Ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxyethanol	-	-	Readily

12. ECOLOGICAL INFORMATIONBioaccumulative potential

Ingredient name	Log _P _{ow}	BCF	Potential
2-butoxyethanol	0.83	-	low

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

European waste catalogue (EWC) : The European Waste Catalogue classification of this product, when disposed of as waste, is: 08 01 15* aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances. If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

Hazardous waste : Yes.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

International transport regulations

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-

PG* : Packing group

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

15. REGULATORY INFORMATION

EU regulations : The product is determined as not being dangerous according to the requirements of the DPD.

Risk phrases : This product is not classified according to EU legislation.

VOC for Ready-for-Use Mixture : IIA/i. One-pack performance coatings. EU limit values: 140g/l (2007) 140g/l (2010.)
This product contains a maximum of 77 g/l VOC.

Europe inventory : Not determined.

Other EU regulations

Additional warning phrases : Safety Data Sheet available for professional user on request.

CN code : 3209 10 00

16. OTHER INFORMATION

Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK) : R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.
R36/38- Irritating to eyes and skin.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

☑ Indicates information that has changed from previously issued version.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties. ©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.