



## SAFETY DATA SHEET

### Anglo Floor Paint & Anglo Floor Paint Epoxy Ester Grade

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME                      Anglo Floor Paint & Anglo Floor Paint Epoxy Ester Grade

SUPPLIER                              Anglo Building Products Ltd  
 RUST-OLEUM UK Ltd  
 Unit 6, Spitfire Close  
 Coventry Business Park  
 Coventry  
 CV5 6UR  
 +44 (0) 2476 717 329  
 +44 (0) 2476 718 930  
 info.uk@ro-m.com

#### 2 HAZARDS IDENTIFICATION

Flammable.

CLASSIFICATION                      R10.

#### ENVIRONMENT

The product is not expected to be hazardous to the environment.

#### PHYSICAL AND CHEMICAL HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

#### HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	< 1%	R10 Xi;R36
BAS 40	265-150-3	64742-48-9	10-30%	Xn;R65. R10,R66.
cozirc driers			< 1%	Xn;R65. Mut 3;R68. R42/43.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT; KEROSENE - UNSPECIFIED	265-149-8	64742-47-8	10-30%	Xn;R65
ETHYL METHYL KETOXIME	202-496-6	96-29-7	< 1%	Carc3;R40 Xn;R21 R43 Xi;R41
ISO-BUTANOL	201-148-0	78-83-1	< 1%	R10 Xi;R37/38,R41 R67
Stoddard solvent			< 1%	Xn;R65. N;R51/53. R10,R66.
White Spirit		64742-82-1	1-5%	Xn;R65. N;R51/53. R10.
XYLENE	215-535-7	1330-20-7	< 1%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

The Data Shown is in accordance with the latest EC Directives.

#### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

#### INHALATION

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

#### INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

## Anglo Floor Paint & Anglo Floor Paint Epoxy Ester Grade

### SKIN CONTACT

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Use: Alcohol resistant foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

### SPECIFIC HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container

### SPILL CLEAN UP METHODS

Keep combustibles away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Wash contaminated area with water. Wash thoroughly after dealing with a spillage.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Do not use contact lenses. Avoid spilling, skin and eye contact. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Store under well-ventilated conditions at a temperature below 25°C.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
2-METHOXY-1-METHYLETHYL ACETATE	OES	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)
ISO-BUTANOL	OES	50 ppm	154 mg/m3	75 ppm	231 mg/m3
XYLENE	OES	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

### HAND PROTECTION

Protective gloves and goggles must be used if there is a risk of direct contact or splash.

## Anglo Floor Paint & Anglo Floor Paint Epoxy Ester Grade

### EYE PROTECTION

Contact lenses should not be worn when working with this chemical! Wear approved safety goggles.

### OTHER PROTECTION

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower.

### HYGIENE MEASURES

Wash promptly if skin becomes contaminated. Promptly remove non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Misc. colours		
SOLUBILITY	Immiscible with water		
RELATIVE DENSITY	Approx. 1.0	VISCOSITY	>7.0 cps 40C
FLASH POINT (°C)	40C	VOLATILE ORGANIC COMPOUND (VOC)	500 g/litre

## 10 STABILITY AND REACTIVITY

### STABILITY

No particular stability concerns.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

### INGESTION

Gastrointestinal symptoms, including upset stomach.

### SKIN CONTACT

Repeated exposure may cause skin dryness or cracking.

### EYE CONTACT

Irritating and may cause redness and pain.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

The product is not expected to be hazardous to the environment.

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

### DISPOSAL METHODS

Absorb in vermiculite or dry sand, dispose in licensed hazardous waste. Make sure containers are empty before discarding (explosion risk).

## 14 TRANSPORT INFORMATION



## Anglo Floor Paint & Anglo Floor Paint Epoxy Ester Grade

PROPER SHIPPING NAME	PAINT RELATED MATERIAL		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	3Y
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	III	EMS	F-E, S-E
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	III		

### 15 REGULATORY INFORMATION

**RISK PHRASES**

R10 Flammable.

**SAFETY PHRASES**

S51 Use only in well-ventilated areas.

S60 This material and its container must be disposed of as hazardous waste.

P14 Contains coziirc driers,ETHYL METHYL KETOXIME. May produce an allergic reaction.

**NATIONAL REGULATIONS**

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Worplace Exposure Limits 2005 (EH40)

### 16 OTHER INFORMATION

REVISION DATE 09/06/2006

REV. NO./REPL. SDS GENERATED 2

**RISK PHRASES IN FULL**

- R10 Flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R21 Harmful in contact with skin.
- R36 Irritating to eyes.
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- R40 Limited evidence of a carcinogenic effect.
- R41 Risk of serious damage to eyes.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R43 May cause sensitisation by skin contact.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- R68 Possible risk of irreversible effects.